

Opto Engine LLC

Data sheet

Rev. 0912

MDL-III-1560R/1~200mW


INFRARED DIODE LASER At 1560nm

Diode infrared laser module at 1560 nm, is made features of ultra compact, long lifetime, low cost and easy operating, which is used in measurement, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	1560±10		
Output power (mW)	>1, 10, 50, 100, ..., 200		
Energy distribution	Even		
Beam Spot	Round		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Warm-up time (minutes)	<5		
Beam divergence, full angle (mrad)	<8.0		
Dimensions of beam at the aperture (mm)	~2.0		
Beam height from base plate (mm)	24.8		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III-1560R	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
<p>140. 8(L)×73(W)×46. 2(H) mm³, 0.6kg</p>	<p>154 (L) ×155(W) ×95 (H) mm³, 1.5kg</p>	<p>133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>	<p>100 (L) ×60(W) ×56 (H) mm³, 0.2kg</p>