

Opto Engine LLC

Data sheet

Rev. 0912

MDL-III-915/1~1500mW


INFRARED DIODE LASER AT 915nm





Diode infrared laser module at 915 nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in measurement, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	915±5		
Output power (mW)	>1, 100, 200, 300, ..., 1500		
Transverse mode	Near TE ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Warm-up time (minutes)	<5		
M ² factor	<20		
Beam divergence, full angle (mrad)	<3.0		
Dimensions of beam at the aperture (mm)	~5×8		
Beam height from base plate (mm)	24.8		
Polarization ratio	>50:1		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
TTL / Analog modulation	Optional, 2kHz or higher (on request, up to 30kHz)		
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III-915	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
			
140.8(L)×73(W)×46.2(H) mm ³ , 0.6kg	154 (L) ×155(W) ×95 (H) mm ³ , 1.5kg	133 (L) ×130(W) ×65 (H) mm ³ , 1.2kg	100 (L) ×60(W) ×56 (H) mm ³ , 0.2kg
