

# Opto Engine LLC

## Data sheet

Rev. 0912

MLL-III-635 /1~500mW

### LOW NOISE RED LASER At 635nm





Low noise red diode laser 635nm is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.



#### SPECIFICATIONS

Wavelength (nm)	635±5		
Output power (mW)	>1, 100, 200, ... , 500		
Transverse mode	Near TE <sub>00</sub>		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Noise of amplitude (rms, 1~20MHz)	<1%		
Warm-up time (minutes)	<5		
M <sup>2</sup> factor	<20		
Beam divergence, full angle (mrad)	<2.5		
Dimensions of beam at the aperture (mm)	~5×8		
Beam height from base plate (mm)	24. 8		
Polarization ratio	>50:1		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
TTL / Analog modulation	Optional, 2kHz or higher (on request, up to 30kHz)		
Expected lifetime (hours)	10000		
Warranty	1 year		



MLL-III-635	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
			
140. 8(L)×73(W) ×46. 2(H) mm <sup>3</sup> , 0.6kg	154 (L) ×155(W) ×95 (H) mm <sup>3</sup> , 1.5kg	133 (L) ×130(W) ×65 (H) mm <sup>3</sup> , 1.2kg	100 (L) ×60(W) ×56 (H) mm <sup>3</sup> , 0.2kg
